

CERTIFICATE

of constancy of performance 1922 - CPR - 1680

In compliance with Regulation (EU) 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Wood-based panels for use in construction

Fibreboard (or Medium density fibreboard), melamine faced fiber for internal use as structural components in dry conditions MDF. FR, reaction to fire class B-s2, d0

(with the performance listed, see Annexes I to 1922-CPR-1680 that is an inseparable part of this certificate)

placed on the market under the name or trade mark of

Limited Liability Company "KASTAMONU INTEGRATED WOOD INDUSTRY" 423600, Russian Federation, Tatarstan, Yelabuga, SEZ "Alabuga" territory, SH-3 Street, building 3/3

and produced in the manufacturing plant

Limited Liability Company "KASTAMONU INTEGRATED WOOD INDUSTRY" 423600, Russian Federation, Tatarstan, Yelabuga, SEZ "Alabuga" territory, SH-3 Street, building 3/3

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

EN 13986:2004+A1:2015

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on 29.10.2021 and will remain valid until 29.10.2022 as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body. The certificate is supported through annual surveillance audit and is reissued after each surveillance audit. The validity of the certificate may be confirmed in the CE register at the web address www.dedal-bg.net.









Issued: Burgas, 29 October 2021

Ref. No. 01-00



ANNEX I TO CERTIFICATE OF CONSTANCY OF PERFORMANCE 1922 - CPR - 1680/29.10.2021 (page 1 of 1)

Performance list, acc. to EN 13986:2004+A1:2015

Characteristics, dimension	Method	Value/Result Thickness 16 mm
Determination of swelling in thickness, %	EN 317	Max. 12
Tensile strength, N/mm ²	EN 319	Min. 0,55
Bending strength, N/mm ²	EN 310	Min. 20
Modulus of elasticity, N/mm ²	EN 310	Min. 2200
Formaldehyde, Class	EN 717-1	E1
Density, kg/m ³	EN 323	>600
Reaction to fire Class acc.to EN 13501-1	EN 13823, EN ISO 11925-2	B-s2, d0
Sound absorption, coefficient	Table 10 of EN 13986+A1	0,10
Thermal conductivity, W/(m · K)	Table 11 of EN 13986+A1	0,14

This certificate was first issued on 29.10.2021 and will remain valid until 29.10.2022 as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body. The certificate is supported through annual surveillance audit and is reissued after each surveillance audit. The validity of the certificate may be confirmed in the CE register at the web address www.dedal-bg.net.









Issued: Burgas, 29 October 2021 Ref. No. 01-00